

AdVantEdge DWS-2S-2710-02

The DWS-2S-2710-02 is a dual stage water treatment approach with an integrated system design, ideal for under-counter household use. The system includes two selected 2.75 x 9.75 inch arsenic removal cartridges, housing components, i.e., sumps, caps, mounting bracket, faucet (lead-free), shut-off device, and tubing for a complete unit. AdEdge Technologies, Inc. supplies both the system components and replacement cartridges. The system is available to qualified water treatment distributors and dealers for subsequent re-sale to end users. Replacement cartridges are available through AdVantEdge authorized distributors.



Specifications

Arsenic Cartridge
Materials Housing
Mounting
Faucet
Shut Off Device
Arsenic media
Water source
NSF testing
Box/Packaging

Model: DWS-2S-2710-02

Two 10 inch standard (2.75 x 9.75 inch); AdVantEdge Model AD2710S
Injection molded polypropelene
Painted metal mounting bracket
Lead-free faucet with ¼ inch tubing
Mechanical countdown shut-off device mounted on bracket
AdEdge custom AD33L product
Potable water of known microbiological quality (microbiologically safe)
Components tested in accordance with NSF protocols, no specific listings
Plain white box, with or without Label

Performance

Rated Cartridge Life 1000 gallons
Arsenic concentration Up to 50 ppb influent arsenic
Replacement Every 12 months or 1000 gallons, whichever comes first
Rated flow rate 0.5 gpm
Parameters AD2710S: arsenic

Contact your local dealer: